

- It is completely produced by original "Polyethylene Raw Material" with blow molding technique.
- There is no any non-standard (recycled) raw material inside.
- > Seat and back rest are with double walls and durable against impacts. In addition to that, there are ribs under the seat to increase durability.
- In order to make the seat more durable to UV and to the external factors, UV stabilizer additive is used.
- Color fastness dyestuffs are us ed is in maximum level in order to avoid discoloration.
- ▶ It is with TS EN 13200-4 and TS EN 12727 and TS EN 13200-4 certificates and production is made according to ISO 9001:2015 ISO 14001:2015 OHSAS 18001-2007 Quality Management System.
- ▶ It has orthopedic seating feature and structure of legs and back rest is very comfortable.
- It is in a structure that pushes the body towards back side and has a design that prevents slipping while seated.
- Metal parts, composed of two components which are installed the seat and back rest produced by 5 mm thick plates. With these components, seat and back rest connected to each other and 12 mm thick needle is used in this connection. The front part of the Stadium
- Seats designed in a way that, seats can not be pulled out from the seating area.
- ▶ The metal structure in seating part is designed to support the seating part.
- ▶ With the stopper that is added to seating metal structure, the sound due to the closure of seat is ceased.
- ▶ Metal legs and connection parts are covered with electrostatic paint or galvanised. With this for long years corrosion is avoided.
- Features of the product can change according to the place and physical conditions of the place.
- According to customer requests, our seats can be produced with UV Stabilizer Additives, Flame Retardant Additives, and Colour Fastness Additives.
- As it is folded through its center of gravity without a spring, there is no any malfunction in folding mechanism.
- ▶ It includes oval label place with size of 54x83 mm in front of back rest and it includes oval numbering place with size of 29x44 mm at the bottom of seating part that is seen when folded.
- The seat is installed to the wall and has 3 screw holes two is at the top and one is at the bottom.
- The dimensions was calculated for the riser height which min. 53 cm and max. 65 cm. Please contact us for different riser height requests.
- ISO 14001:2015 Environmental Management System, ISO 45001:2018 Occupational Health and Safety Management System.

